# **F3 SERIES**

F3 offers the state of the art Radio Frequency (RFID), Bluetooth technology and stable mechanical design to ensure guest satisfaction.

F3 has wisely developed installation system to make the lock exactly fit to the door. After the first correct installation F3 will never move on the door. The technical service maintanance will follow this installation to prevent wrong installations.

Anti-Cloning technology, Europe and US std mortise options.

Hidden mechanical ovveride key option in case of emergency.



## ELEKTRONİK KİLİT Özellikler

| Lock Unlocking Method              | Card & Bluetooth.<br>Remote access with Gateway |  |  |
|------------------------------------|---|--|--|
| Mechanical Key                     | Available                                       |  |  |
| Start Time                         | <1 second                                       |  |  |
| Create Admin Account               | Available                                       |  |  |
| Unlock via Card                    | Available                                       |  |  |
| Unlock via Bluetooth from a mobile | Available                                       |  |  |
| Operating Voltage                  | 6V, 4 pieces of Akalin                          |  |  |
| Static Power Consumption           | <4µA  |  |  |
| Dynamic Power Consumption          | 200 mA  |  |  |
| Operating Temperature              | Between -20 °C and 50 °C                        |  |  |
| Maximum Humidity                   | ≤ %80   |  |  |
| Door Thickness                     | 38~60mm   |  |  |



| Door Thickness     | 38~60mm      |
|--------------------|--------------|
| Sensor Distance    | 3~5cm        |
| Lock Weight        | 3.5kg        |
| Battery Life       | 12~16 months |
| Voltage Alarm      | Yes          |
| Lock Alarm         | Available    |
| TTLOCK and TTHOTEL | Yes          |

| Model | Mortise (Lock Body) Features |                        |                  |                | Battery              |               |            |        |
|-------|------------------------------|------------------------|------------------|----------------|----------------------|---------------|------------|--------|
| F3    | Mortise                      | Min. Door<br>Thickness | Mortise<br>Depth | Center<br>(mm) | Mortise<br>Thickness | Туре          | Motor      | Weight |
| E2    | Euro                         | 32 mm                  | 85 mm            | 55 mm          | 23mm                 | 4xAA<br>4xAAA | In Mortise | 2,50   |
| E4    | TS EN 12209                  | 30 mm                  | 66 mm            | 40 mm          | 22mm                 | 4xAA          | In Body    | 2,45   |
| E5    | 50x85 Euro                   | 30 mm                  | 76 mm            | 50 mm          | 22mm                 | 4xAA          | In Body    | 2,30   |
| A3    | ANSI                         | 36 mm                  | 90 mm            | 62 mm          | 26mm                 | 4xAA          | In Mortise | 2,55   |
| к     | Knob                         | 32 mm                  | 60-80 mm         | 50-60-70 mm    | 24mm                 | 4xAA<br>4xAAA | In Body    | 1,90   |

| F3 Series<br>Mortise<br>Options | A1 - A2<br>Mortise   | E-2<br>Mortise   | E3-E1<br>Mortise   | K6-K7<br>Mortise   |
|---------------------------------|--|--|--|--|
| Anti Friction Latch             | <ul> <li>Image: A second s</li></ul> | <ul> <li>Image: A second s</li></ul> | ×  | <ul> <li>Image: A second s</li></ul> |
| Anti-Pick (Theft) Latch         | ~  | ~  | ×  | ×  |
| Deadbolt                        | <ul> <li>Image: A second s</li></ul> | <ul> <li>Image: A second s</li></ul> | <ul> <li>Image: A second s</li></ul> | ×  |
| Anti-Panic Exit                 | $\checkmark$   | $\checkmark$   | $\checkmark$   | $\checkmark$   |
| Auto-Locking Function           | ×  | ×  | <ul> <li>Image: A second s</li></ul> | ×  |
| Min Door Thickness              | 40 MM  | 30 MM  | 30 MM  | 32 MM  |
| Cylinder Type                   | ANSI   | EURO   | EURO   | EURO   |
| Electronic DND Function         | $\checkmark$   | <ul> <li>✓</li> </ul>  | $\checkmark$   | $\checkmark$   |



### **Gateway / Bridge Features**

- The lock can be remotely managed and unlocked (e.g., from a reception) using Bluetooth, card, or gateway.
- Keys can be created for unlocking the lock from other mobile devices.
- Opening logs can be tracked remotely.
- You can view the lock's battery status remotely.
- All settings are configured via the TTLock and TTHotel software. It is easy to use.
- With the gateway, you can add scenarios to your locks using Google Home Assistant and Amazon Alexa and benefit from the remote voice command unlocking feature.

## F3 RFID ELECTRONIC LOCKING System Features

- Stable reading speed
- Long Battery Life.
- Works with paper card, ISO cards, wristbands, keychains etc
- Even dia 14mm paper label cards can be identified
- Powered by 4pcs of Alkaline AA-AAA batteries. 2 years battery life
- Led and sound allerts
- Classic Hotel Lock Desing

### **Body / Lock Features**

- SUS 304 Stainless Steel Body
- Optional Outdoor PVD Coating
- Special Installation System to ensure the stability
- Very easy to maintain.
- Extra Strong Desing
- EUR 55x75 or ANSI Mortise Options
- Compatible with upto 120 min. Fire rated doors
- CE, FCC, ISO
- Anti-Friction Latch
- DND Function and Anti-Panic Function
- Anti-Pick (Theft) Latch
- EUR Std Cylinder for E1-E2 Mortises
- ANSI Special Cylinder for A1-A2 Mortises

