S7 SERIES

S7 offers the state of the art Radio Frequency (RFID) technology and stable mechanical design to ensure guest satisfaction.

S7 has wisely developed installation system to make the lock exactly fit to the door. After the first correct installation S7 will never move on the door. The technical service maintanance will follow this installation to prevent wrong installations.

Anti-Cloning technology, Europe and US std mortise options.

Hidden mechanical ovveride key option in case of emergency.



ELEKTRONİK KİLİT Özellikler



Card & Bluetooth. Remote access with Gateway

Mechanical Key

Available

Start Time

<1 second

Create Admin Account

Lock Unlocking Method

Available

Unlock via Card

Unlock via Bluetooth from a mobile

Available

Operating Voltage

6V, 4 pieces of Akalin

Static Power Consumption

<4µA

Dynamic Power Consumption

. . . .

Operating Temperature

Between -20 °C and 50 °C

Maximum Humidity

≤ %80

Door Thickness

38~60mm









Sensor Distance3~5cmLock Weight3.5kgBattery Life12~16 monthsVoltage AlarmYesLock AlarmAvailableTTLOCK and TTHOTELYes



Model	Mortise (Lock Body) Features					Battery		
S 7	Mortise	Min. Door Thickness	Mortise Depth	Center (mm)	Mortise Thickness	Type	Motor	Weight
E2	Euro	32 mm	85 mm	55 mm	23mm	4xAA	In Mortise	2,50
E4	TS EN 12209	30 mm	66 mm	40 mm	22mm	4xAA	In Body	2,45
E5	50x85 Euro	30 mm	76 mm	50 mm	22mm	4xAA	In Body	2,30
A3	ANSI	36 mm	90 mm	62 mm	26mm	4xAA	In Mortise	2,55
E3	Fireproof	36 mm	80 mm	50 mm	22mm	4xAA	In Body	2,60

S7 Series Mortise Options	A1 - A2 Mortise	E-2 Mortise	E3-E1 Mortise	K6-K7 Mortise	
Anti Friction Latch	~	✓	X	✓	
Anti-Pick (Theft) Latch	✓	✓	×	×	
Deadbolt	✓	✓	~	X	
Anti-Panic	✓	✓	✓	✓	
Auto-Locking Function	X	X	✓	X	
Min Door Thickness	40 MM	30 MM	30 MM	32 MM	
Cylinder Type	ANSI	EURO	EURO	EURO	
Electronic DND Function	✓	✓	✓	✓	





